


# Shenzhen TOPLED Optotech Co., Ltd

### Catalog

- Enterprise profile
- Enterprise culture
- Certificates
- Main products
- Successful cases
- Application
- > Find TOPLED

## Enterprise profile

ShenZhen TOPLED Optotech Co., Ltd,(herein after call TOPLED), headquartered in Bao'an District, Shenzhen, China, is a professional led manufacturer established in May 2006, with a registered capital of RMB21 million and 14,000 square meters factory area. TOPLED'S business covers indoor and outdoor led display, led curtain, LED components, LED multimedia advertising screen, stadium display, highway and transportation changeable message sign, rental display, indoor and outdoor led lighting etc. TOPLED is a high-tech company specializing in LED researching, manufacturing, marketing and engineering service to provide customers with high-quality services.









### Enterprise culture

Mission: Continuously forge ahead and innovation!

Vision: TOPLED shine your daily life!

Concept: Win-win cooperation achieves your dream!

**Morality:** Reputation premier, honesty and keeping improving!

Style: Fast, efficient and team building!

Slogan: We promise it, we realize it!

### Certificates







Besides, we have more than 23 technology patents for led display

### Feature products

- 1. Indoor SMD full color die-casting aluminum cabinet: P1.875, P2.0, P2.5, P2.98, P3.91.
- 2. Indoor full color: P2, P2.5, P3, P4, P5, P6.
- 3. Outdoor SMD full color die-casting aluminum cabinet: P3.75, P3.91, P4.81, P5.95.
- 4. Indoor SMD full color steel cabinet: P4, P4.8, P5, P6, P8, P10, P8 energy-saving screen, P10 energy-saving screen

### Parameters

Pixel Pitch	1.5	1.875	1.923
Physical Density	444,444	284,444	270,410
LED Configuration	1RGB	1RGB	1RGB
LED type	SMD1010	SMD1515	SMD1515
Module Size	240×180	240×180	200×300
Module Resolution	160X120	128×96	104X156
Driving Mode	Constant	Constant	Constant
	Current Drive	Current Drive	Current Drive
Scanning Mode	1/30	1/32	1/26
Horizontal Viewing Angle	160	140	160
Vertical Viewing Angle	140	140	140
Brightness	≥1600	≥1500	≥1200
Grey Scale	16bit	16bit	16bit
Refresh Rate	≥3840	≥3840	≥3840
Cabinet Resolution	320X360	256×288	208X156
Cabinet Average Power Consumption	77	49	35
Cabinet Size	480X540	480×540	400X300
Cabinet Weight	8.1	8	4.6
Cabinet Thickness	85	85	66
Cabinet Material	Die-casting Aluminum		
Input Voltage	AC 110V~220V +/-10%		
Refresh Frame Frequency	≥60		
Protection Level	IP43		
Working Environment	Indoor		
Working Temperature	-40° -+65°		
Storage Humidity Range	10%~90%		
Life Span	100,000		



Module front view



Module rear view

Features: Non-reflective screen, Perfect Image, Light Weight, Elegant Appearance, Easy Setup, Energy -saving





Die-casting aluminum cabinet

### Successful cases

DongGuan Guanghui Edifice 314.57 m<sup>2</sup> P10 SMD OUTDOOR Display (March, 2016)





Guangdong XIWUN P8 outdoor full color truck display (2015) totally 75 sets



Guangzhou Asian Games Swimming and Diving Halls LED screen

Expo 2010 Shanghai Guangdong Pavilion ribbon panel









Indoor SMD full color P3 six-sided 3D Screens in Jiangsu province.







American 'CARIBBEAN PRINCESS' stage screen





Manila Square two pieces of P20 outdoor full color screens in Philippine, totally 249.6sqm







# LED Display Application



### Contact us

Address: Area C ,2<sup>nd</sup> floor, Building C, No.6 Tangwei Industrial Avenue, Fuyong Boulevard, Baoan District, Shenzhen, Guangdong, China .



#### **Oversea Marketing Department**

Stephanie Peng

Tel:0086755 2650 0905/0906 Ext:8026

Mobile Phone: 0086-180 9899 2369

Email: stephanie.peng@cntopleds.com

Skype:stephanie.peng\_2

**Crystal Chen** 

Tel:0086755 2650 0905/0906 Ext:8047

Mobile Phone: 0086-188 1682 8620

Email: crystal.chen@cntopleds.com

Skype: Crystal.chen\_13



Website: www.cntopleds.com

Website on alibaba.com: topleds.en.alibaba.com